




SB 999l UN 50H

50H/Y/.../D/BAM 16295-CPT/2560/1271



Art.-Nr.: 81941995

Technical Data*1

External Dimensions L x W x H (mm)	1600 x 1200 x 790 mm (with lid 1619 x 1219 x 862 mm)	Internal Dimensions L x W x H (mm)	1520 x 1120 x 590 mm
Weight(kg)	73,5 kg	Volume (l)	999 l
Material*2	PE		
Load capacity (kg)	 Stacking Load 1271kg	 Holding Capacity 1271kg	 Dynamic Load

Characteristics

Colour: light grey
Runners: 4, unverschweißt
Stackable
Temperature stability: -30°C to +40°C, briefly up to +90°C
Resistant to most chemicals and cleaning agents
Food-safe. HACCP compliant
Container is based on DIN EN 13626 and DIN EN ISO 12048
The design type complies with the test provisions of the international regulations for packagings for the transport of dangerous goods (packaging groups II and III)

Options



Transponder(RFID)

Loading quantities (Pcs / Approximate amount)

 Container	Container 20': - Container 40': -	Container 40' High Cube: 32 Conventional trailer 45' high cube container: 32
 Truck	MEGA-Trailer: 32	Jumbo: 32

Labelling

Customised printing and numbering available on request depending on quantity. Position upon consultation.



*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.

*2 Our service team is pleased to be at your disposal if you require exact information about material compositions.